

# Aquaease<sup>®</sup> SEL 323

Aquaease SEL 323 is liquid highly alkaline product developed for electro cleaning ferrous metals.

It contains a unique wetting system that is stable in this high caustic containing product.

### **Features & Benefits**

| High conductivity | Minimizes scale build-up on |
|-------------------|-----------------------------|
|                   | plate coils                 |

## **Typical Applications**

• Electro cleaner in plating lines

#### **Operating Conditions**

| Concentration   | 5% – 20%  |
|-----------------|---|
| Temperature     | 100°F – 200°F (38°C – 93°C)                                       |
| Current density | 40 – 80 amps/ft <sup>2</sup><br>(4.0 – 8.0 amps/dm <sup>2</sup> ) |
| Equipment       | Mild steel tanks and heating coils                                |

Note: The above concentrations given are for a wide variety of applications. For the average jobs, the concentration may range between 8% to 11% by volume.

#### **Titration Method**

- 1. Pipette 10 mL sample of Aquaease SEL 323 solution into a 250 mL Erlenmeyer flask.
- 2. Add 50 mL of water to Erlenmeyer flask.
- 3. Add 5 drops Phenolphthalein indicator.
- 4. Titrate with 0.5 N Hydrochloric Acid until the solution becomes colorless.
- 5. Record mL used.

Calculation

Concentration = mL 0.5 N HCl x 0.488







#### **Waste Disposal**

Discharge rinse waters and spent solutions to a permitted disposal system. In order to be completely informed on the latest regulations for your area, please contact the local authorities.

## Caution

Consult Safety Data Sheet prior to handling Aquaease SEL 323. Avoid skin, eye and oral contact. Wear protective clothing, gloves and goggles when handling the product. Flush exposed areas immediately with clean, cold water. Contact a doctor immediately in case of injury.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

## Our people. Your problem solvers.

For more information on this process please call us at 1-800-648-3412

or techservice@hubbardhall.com











